



Model Medical Implant STK 113	
Voltage / Frequency	V / Hz 230 / 50
Absorption	A/KW 16/3,2
Min/Max water pressure	bar/psig 3-6/43,5-87
Min/Max air pressure	bar/psig 6-8/87-116
Working temperatures	°C/°F° +5°_+40° / +41°_+104°
Air connection	/ G 1/2"
Electrical connection	/ Socket CEE 2P+T 16A 220V
Water connection	/ G 1/2"
Compressed air flow rate	L/min - gal/min 400 - 105,6
Water flow rate	L/min - gal/min 8 - 2,1
Type of water	/ Industrial
Drain connection	Hose mm/in Ø 40 - Ø 1,57

04	Updated data table	S.P.	17/10/2019
Rev	Description:	Author	Date

Drawn by:	S.P.	Date:	24/10/2018	Released by:	S.P.	Date:	10/08/2019
Heat treatment:	Surface treatment:	Ecological surface cleaning systems using sodium bicarbonate					

Material:	Mass:	598 Kg	Category:	ADM	Division:	Medical	Tolerance:	UNI EN 22768-mk
Description:	Medical system assembly STK 113	Scale:	120	Sheets:	A3 1/3	Code:		Rev.

Derived from:	12000344	04
---------------	----------	----

BICAR jet