



Medical system model STK 103-110-113	
Voltage / Frequency	V / Hz 230 / 50
Current / Power	A/kW 16/3,2
Min/Max water pressure	bar/psig 3-6/43,5-87
Min/Max air pressure	bar/psig 6-8/87-116
Working temperatures	C°/F° +5°_ +40° / +41°_ +104°
Air connection	/ G 1/2"
Electrical connection	/ CEE 2P+T 16A 220V Socket
Water connection	/ G 1/2"
Air flow rate	L/min - gal/min 400 - 105,6
Water flow rate	L/min - gal/min 8 - 2,1
Type of water	/ Industrial
Drain connection	Hose mm/in $\varnothing 40 - \varnothing 1,57$

ABOUT COMPRESSED AIR AND WATER CONNECTIONS WE SUGGEST TO FIT IN THEIR CORRESPONDENCE A TAP IN CASE OF SERVICE.

Drawn by: S.P.	Date: 28/05/2018	Released by: S.P.	Date: 30/03/2021	BICAR jet	
Heat treatment:	Surface treatment:	Ecological surface cleaning systems using sodium bicarbonate			
Material:	Mass: Kg	Category: LAY	Division: Medical	Tolerance: UNI EN 22768-mK	
Description: Layout utilities installation for STK 103-110-113	Scale: 1:50	Sheets: A3 2/2	Derived by:	Code: 18000001	Rev: 03